

# Product List

## 产品列表

分类 Category	漆膜/导体区分 Insulation/Conductor	标记 Designation	温度等级 Thermal Class(℃)	线径范围 Conductor Diameter(mm)
普通漆包圆铜线 Standard Enameled Round Copper Wire	聚氨酯 Polyurethane	UEW	130~180	0.020~0.80mm
	聚酯 Polyester	PEW	130~180	0.020~0.80mm
高耐热等级 漆包圆铜线 High Thermal Grade Enameled Round Copper Wire	聚酯亚胺 Polyimide	EIW	180~220	0.070~0.80mm
	聚酰胺酰亚胺 Polyamideimide	AIW	220	0.100~0.80mm
超微细漆包圆铜线 Ultra-fine Enameled Round Copper Wire	聚氨酯 Polyurethane	UEW	155~180	0.010~0.02mm
微细自粘漆包线 Fine Self-bonding Enameled Wire	铜 Copper	HB/SB	155~220	0.010~0.15mm
	铜包铝 Copper-clad Aluminum	HB/SB	155~180	0.025~0.15mm
高张力线/合金线 High Tension Wire /Alloy Wire	高张力线 High Tension Wire	HTW/DHT/ SDHT/UDHT	130~220	0.015~0.10mm
	合金线 Alloy Wire	铜银/铜锌/铜锡/铜镍 Copper Silver/Copper Zinc/ Copper Tin/Copper Nickel	130~180	0.020~0.50mm
* 精密小型扁平 漆包线 Fine Rectangular Wire	铜 Copper	FTAIW/FTEIW FTSEIW FTEIAIW/FTUEW	130~220	宽度(Width):0.155~7.5mm 厚度(Thickness):0.02~1.8mm 宽厚比(Width Thickness Ratio):1:25

注: \* 为待产 Coming soon ...